

KVM Console Unit



KVM Console Unit

Accessory

Product Part Number: LN-LCD1701

17" LCD KVM Console (Disassembly design for Keyboard, Touch Pad Mouse)

KVM console module featuring an integrated 17" LCD panel, over-thin keyboard, and touchpad in a 1U rack-mountable housing. With a grade 17" TFT LCD, The highest resolution: 1920*1080 60HZ; the optimum resolution: 1280*1024 60HZ; Compared with traditional keyboards, monitor and mouse, it could save almost 85% space.

Control platform with LCD, keyboard, mouse. 17" LCD screen with high brightness, high clear and high resolution. Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees.

1U height, suitable for 19" standard cabinet installation and metal structure. Ultra thin keyboard with keypad. Mouse touch board with two function button. Front panel with lock to prevent damage by accident. Built-in Or External power. Automatic power on/off. When pulling control platform out from cabinet, the power turns on automatically. When pushing it into the cabinet, the power turns off automatically. Easy use of OSD menu. CE and ROHS certified.



LN-LCD1701 - KVM Module Description		
Type		1 Port
Computer Connection	Direct Connects	1
	Maximum Connects	1
CPU Port Selection		/
Connectors	Console Connector	DB 37PIN
	PC Connector	Monitor, Keyboard / Mouse Switch Module
	Power	1 x DC Jack
	Network Port	/
Key Switch	Connection Port Selection	/
	KVM Reset	KVM Operation Panel Function Keys
	IP Module Reset	/
	IP Module Default	/
LED's	Selected	/
	Online	/
	IP Network	/
Analog Mode	Keyboard / Mouse	USB, PS/2
Resolution (Max)		1920 x 1200 @ 60HZ Local & Remote
Scan Time Interval		3, 5, 10, 15, 20, 30, 40, 60s (3s by default)
Operating Environment	Operating Temperature	-10-50°C
	Storage Temperature	-20-60°C
	Humidity	0-80%RH, No Condensation
Physical Properties	Housing	Plastic
	Dimensions	50*77*24.5 mm
	Weight	0.18 kgs.

LN-LCD1701 - Description		
Type		17" LCD Console
LCD Monitor	Ratio	17" Screen, 4:3
	Video	SXGATFT-LCD
	Visible Square	337.920(H) x 270.336(V)
	Resolution	1280*1024@60HZ(Optimum)/1920*1200@60HZ(Max)
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	Contrast	1000:1 (Typ)
	Backlight	LED
	Pixel Pitch	0.264x0.297 mm
	LEDMTBF	100,000 hours
	Input Power	12V
Keyboard (Demountable design)	Keyboard	100 Keys, Detachable (9 different languages for choose)
	Compatible IBM / AT	Microsoft Windows 9, Me/NT/2000/XP, WIN7, Server 2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using Life	> 1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	> 1000 dots/inch, (40x40/mm)
	Using Life	> 1,000,000 Times
Installation Dimension	407*445*45 mm	
Weight	6.15 kgs.	

KVM Console Unit

Accessory

Product Part Number: LN-LCD1708

17" LCD KVM SWITCH in 8 ports, combo support (USB/PS.2), combo cable included.

LCD KVM Switch featuring an integrated 17" LCD panel, over-thin keyboard and touchpad in a 1U rack-mountable housing. With a grade 17" TFT LCD, The highest resolution: 1920*1080 60HZ; the optimum resolution: 1280*1024 60HZ. Compared with traditional keyboards, monitor and mouse, it could save almost 85% space.

Control platform with LCD, keyboard, mouse and multiple ports KVM switch. 17" LCD screen with high brightness, high clear and high resolution. Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees.

1U height, suitable for 19" standard cabinet installation and metal structure. Ultra thin keyboard with keypad. Mouse touch board with two function button. Front panel with lock to prevent damage by accident. Built-in Or External power. Automatic power on/off. When pulling control platform out from cabinet, the power turns on automatically. When pushing it into the cabinet, the power turns off automatically. Easy use of OSD menu. CE and ROHS certified.

Switch; One control platform can control 8 computers by direct connection. One control platform can control 128 computers by 3 level cascade connection. Be compatible with PS/2, USB standard interface. Support VGA, SVGA, XGA video input. Accord with DDC, DDC2, DDC2B standard and VESA standard. Support resolution of 1280*1024 60HZ Support multiple operating systems: Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10.

LN-LCD1708 - Description		
Type		17" LCD Console
LCD Monitor	Ratio	17" Screen, 4:3
	Video	SXGATFT-LCD
	Visible Square	337.920(H) x 270.336(V)
	Resolution	1280*1024@60HZ(Optimum)/1920*1200@60HZ(Max)
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	Contrast	1000:1 (Typ)
	Backlight	LED
	Pixel Pitch	0.264x0.297 mm
	LEDMTBF	100,000 hours
	Input Power	12V
Keyboard (Demountable design)	Keyboard	100 Keys, Detachable (9 different languages for choose)
	Compatible	Microsoft Windows 9, Me/NT/2000/XP, WIN7, Server 2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using Life	> 1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	> 1000 dots/inch, (40x40/mm)
	Using Life	> 1,000,000 Times
Installation Dimension	407*445*45 mm	
Weight	6.15 kgs.	



LN-LCD1708 - KVM Module Description			
Type			8 Port
Computer Connection	Direct Connects		8
	Maximum Connects		128
CPU Port Selection			OSD Menu, Front Panel Buttons, Hot Key, IP Remote Control (Optional)
Connectors	Console Connector		DB 37PIN
	PC Connector	Monitor, Keyboard / Mouse Switch Module	8 x VGA DB15, Female Blue
	Power		1 x DC Jack
	Network Port		1 x RJ45 (Optional)
Key Switch	Connection Port Selection		KVM Operation Panel Digital Keys
	KVM Reset		KVM Operation Panel Digital Keys
	IP Module Reset		1 x semi-embedded key
	IP Module Default		1 x semi-embedded key
LED's	Selected		Nixie Tube Display
	Online		8 x Red
	IP Network		1 x Green, 1 x Orange
Analog Mode	Keyboard / Mouse		USB, PS/2
Resolution (Max)			1920 x 1200 @ 60HZ Local & Remote
Scan Time Interval			3, 5, 10, 15, 20, 30, 40, 60s (3s by default)
Operating Environment	Operating Temperature		-10-50°C
	Storage Temperature		-20-60°C
	Humidity		0-80%RH, No Condensation
Physical Properties	Housing		Metal
	Dimensions		148.4*445*45 mm
	Weight		3.32 kgs.

KVM Console Unit

Accessory

Product Part Number : LN-LCD1716

17" LCD KVM SWITCH in 16 ports, combo support (USB/PS.2), combo cable included.

LCD KVM Switch featuring an integrated 17" LCD panel, over-thin keyboard, and touchpad in a 1U rack-mountable housing. With a grade 17" TFT LCD, The highest resolution: 1920*1080 60HZ; the optimum resolution: 1280*1024 60HZ. Compared with traditional keyboards, monitor and mouse, it could save almost 85% space.

Control platform with LCD, keyboard, mouse and multiple ports KVM switch. 17" LCD screen with high brightness, high clear and high resolution. Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees.

1U height, suitable for 19" standard cabinet installation and metal structure. Ultra thin keyboard with keypad. Mouse touch board with two function button. Front panel with lock to prevent damage by accident. Built-in Or External power. Automatic power on/off. When pulling control platform out from cabinet, the power turns on automatically. When pushing it into the cabinet, the power turns off automatically. Easy use of OSD menu. CE and ROHS, FCC certified. With IP function, 1 remote user.

Switch; One control platform can control 16 computers by direct connection. One control platform can control 256 computers by 3 level cascade connection. Be compatible with PS/2, USB standard interface. Support VGA, SVGA, XGA video input. Accord with DDC, DDC2, DDC2B standard and VESA standard. Support resolution of 1280*1024 60HZ. Support multiple operating systems: Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10.

LN-LCD1716 - Description		
Type		17" LCD Console
LCD Monitor	Ratio	17" Screen, 4:3
	Video	SXGATFT-LCD
	Visible Square	337.920(H) x 270.336(V)
	Resolution	1280*1024@60HZ(Optimum)/1920*1200@60HZ(Max)
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	Contrast	1000:1 (Typ)
	Backlight	LED
	Pixel Pitch	0.264x0.297 mm
	LEDMTBF	100,000 hours
	Input Power	12V
Keyboard (Demountable design)	Keyboard	100 Keys, Detachable (9 different languages for choose)
	Compatible	Microsoft Windows 9, Me/NT/2000/XP, WIN7, Server 2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using Life	> 1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	> 1000 dots/inch, (40x40/mm)
	Using Life	> 1,000,000 Times
Installation Dimension	407*445*45 mm	
Weight	6.15 kgs.	



LN-LCD1716 - KVM Module Description			
Type			16 Port
Computer Connection	Direct Connects		16
	Maximum Connects		256
CPU Port Selection			OSD Menu, Front Panel Buttons, Hot Key, IP Remote Control (Optional)
Connectors	Console Connector		DB 37PIN
	PC Connector	Monitor, Keyboard / Mouse Switch Module	16 x VGA DB15, Female Blue
	Power		1 x DC Jack
	Network Port		1 x RJ45 (Optional)
Key Switch	Connection Port Selection		KVM Operation Panel Digital Keys
	KVM Reset		KVM Operation Panel Function Keys
	IP Module Reset		1 x semi-embedded key
	IP Module Default		1 x semi-embedded key
LED's	Selected		Nixie Tube Display
	Online		16 x Red
	IP Network		1 x Green, 1 x Orange
Analog Mode	Keyboard / Mouse		USB, PS/2
Resolution (Max)			1920 x 1200 @ 60HZ Local & Remote
Scan Time Interval			3, 5, 10, 15, 20, 30, 40, 60s (3s by default)
Operating Environment	Operating Temperature		-10-50°C
	Storage Temperature		-20-60°C
	Humidity		0-80%RH, No Condensation
Physical Properties	Housing		Metal
	Dimensions		148.4*445*45 mm
	Weight		4.96 kgs.



CONTACT DETAILS

Headquarters

Address:

Merve Mah. Gazi Cad. No: 17 **Phone:** +90 216 312 26 53
Sancaktepe - İstanbul / TURKEY **Fax** : +90 216 312 09 09

Factory

Address:

20. Cadde No: 14 Eskişehir **Phone:** +90 222 236 24 66 pbx
Organize San. Bölge. 26110 **Fax** : +90 222 236 13 53
Eskişehir / TURKEY

www.lande.com.tr | sales@lande.com.tr

